

## Damages Caused by Liquefaction

- due to stiffness and strength loss in soil materials
  - **rise of buried structure, subsidence of structures, sway of retaining structures**
- due to slide and flow of soil materials
  - lateral flow, **flow failure of fill, slump of fill**
- due to change in vibration properties
  - **increase in natural period**

*(positive and negative effects)*

(some more explanation: L-2-1)

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

1

## Estimated Damage Hanshin-Awaji EQ., 1995


Items	Estimated value (billion yen)
1. Structure (building)	5800.0
2. Railway	343.9
3. Expressway	550.0
4. Public facilities	296.1
5. Harbor	1000.0
6. Reclaimed land area	6.4
7. Facilities for education	335.2
8. Facilities for agriculture, forestry and fisheries	118.1
9. Facilities for health, medical and welfare	173.3
10 Facilities for waste and sewage disposal	4.4
11. Facilities for water supply	54.1
12. Facilities for gas and electricity	420.0
13. Facilities for communication and broadcasting	120.2
14. Facilities of commerce and industry	630.0
15. Other public facilities	75.1
Total	9926.8 billion yen

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

2

## Water Front in Kobe City after 1995 Hyogoken Nambu Earthquake



liquefaction occurred extensively

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

3

## Port Island in Kobe City




grand is covered with boiled sand

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

4

## Rise of buried structures



$V$ ; total volume,  $V'$ ; volume of under ground part  
 $\rho_s$ ; average density of structure,  
 $\rho_{sat}$ ; density of saturated soil

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

5

## Damaged water tank



buried water tank floated up in Niigata Port,  
during 1964 Niigata Earthquake

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

6

## Damaged sewage system




a manhole was lifted by 1.4m due to liquefaction of fill sand during 1993 Kushiro-oki Earthquake

2006/6/22

Mechanics of Geomaterials by J. Takemura

7

## Raise of sewage system



2006/6/22

Mechanics of Geomaterials by J. Takemura

8

## Damaged chemical storage tank




Empty tank floated up  
in 1993 Hokkaido Nansei-oki Earthquake

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

9

## Subsidence of structures



- liquefied ground loses bearing capacity
- structures subside with tilting esp. for asymmetric structures

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

10

## Damaged buildings




some buildings were tilted and subsided in 1964 Niigata Earthquake

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

11

## Sway of retaining structures



- in water front resultant force increases by the factor of three
- sliding and/or subsidence occur

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

12

### Zone of liquefied area in Rokko Island at 1995 Hoguken-Nanbu Eq.




2006/6/22

Mechanics of Geomaterials by J. Takemura

13

### Displacement of quay wall by Kobe Eq. (Port Island)

S&F special issue (1996)



2006/6/22


Mechanics of Geomaterials by J. Takemura

14



## Displacement of quay wall by Kobe Eq. (Rokko Island)

S&F special issue (1996)



2006/6/22


Mechanics of Geomaterials by J. Takemura

15

## Damaged quay wall



[S&F paper L-4-4](#)



many quay walls were damaged due to liquefaction of backfill in 1995 Hyogoken-Nambu Earthquake


2006/6/22

Mechanics of Geomaterials by J. Takemura

16



## Typical section of quay wall in Kobe Port



These three conditions caused **5m** lateral displacement.


[S&F paper L-4-4](#)

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

17

## Observed ground motions and accelerations at Kobe Port




2006/6/22

Mechanics of Geomaterials by J.  
Takemura

18

## High seismic resistant quay walls at Maya Wharf




Seismicity: 0.25

No liquefiable sand  
beneath and behind  
quay wall



HSRQW performed very well against strong motion.



S&F special issue (1996)

2006/6/22

Mechanics of Geomaterials by J. Takemura

19

## Due to slide and flow of soil materials


- Lateral flow
  - pipelines, pile foundations
- Flow failure of fill
  - fill embankments on slope (housing lots, road, rail road), dams
- Slump of fill
  - fill embankments (road, railroad, housing lots), river dike

2006/6/22

Mechanics of Geomaterials by J. Takemura

20

## Lateral flow



- Sloped ground Ground with laterally free

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

21

## Liquefaction in flat area



Ground subsided by 30cm with sand boiling,  
in port island during 1995 Hyogoken-nambu Earthquake


2006/6/22

Mechanics of Geomaterials by J.  
Takemura

22

## Lateral flow in Niigata city

Extensive lateral flow occurred around Shinano River, during 1964 Niigata Earthquake




2006/6/22

Mechanics of Geomaterials by J.  
Takemura

23

## Lateral flow around Bandai Bridge



1962

1964 (after hrs.)

1971

river side slid toward river in 1964 Niigata Earthquake

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

24

## Lateral flow of river side



river sides slid toward river with many parallel cracks,  
in 1964 Niigata Earthquake

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

25

## Collapse of Showa-ohhashi Bridge in 1964 Niigata Earthquake



Bridge piers were distorted by lateral movement of  
foundation ground and girders fell down.

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

26

## Damaged pile foundation in 1964 Niigata Earthquake



pile foundation for a building at river side  
was distorted by lateral flow of liquefied ground

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

27

## Lateral movement of ground in 1995 Hyogoke-Nambeu Earthquak [S&F paper L-4-2](#)



Entire ground surface moved  
1-3m towards north, resulting  
severe damage of not quay walls  
but also concrete piles and buried  
piles



Change the design code  
of of highway bridge  
foundation, considering  
force due to lateral M.


2006/6/22

Mechanics of Geomaterials by J.  
Takemura

28



## Flow failure of fill



reduction of shear strength due to liquefaction leads to slide failure of embankments or dams.

2006/6/22

Mechanics of Geomaterials by J. Takemura


29

## Flow failure of earth dam

San Fernando Dam: Hydraulic fill dam constructed in 1930.



Slide in the Lower San Fernando Dam during 1971 San Francisco Earthquake



2006/6/22

Mechanics of Geomaterials by J. Takemura

30



## Collapsed road fill embankment



a part of road embankment constructed curved slope was slid away, in 1993 Kushiro-oki Earthquake.

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

31

## Slumped embankments in 1993 Kushiro-oki Earthquake




2006/6/22

Mechanics of Geomaterials by J.  
Takemura

32

Due to change in vibration properties

- Increase in natural period




2006/6/22

Mechanics of Geomaterials by J. Takemura

33

## change of vibration properties due to liquefaction



2006/6/22

Mechanics of Geomaterials by J. Takemura

34

## Damaged cement storage tank due to resonance with liquefied ground



2006/6/22

Mechanics of Geomaterials by J.  
Takemura

35

## Countermeasures against Liquefaction -preventing the required condition for liquefaction-

- **Cyclic shear deformation**
- **Uniformly graded sand ground**
  - silt or clay exhibits no dilatancy behavior
  - liquefaction is not sustainable in gravel (high permeability prevents the accumulation of  $\Delta u$ )
- **Loose ground**
  - loose grounds show large volume reduction
- **High ground water table**
  - liquefaction is not sustainable in dry condition
  - ground water keeps liquefaction

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

36

## Remedial Methods against Liquefaction

- Improvement of the properties of ground and soil structure
  - replacement, strengthen, densification
- Enhancement of drainage
  - lowering ground water table, control of pore water pressure increase
- Reinforcement of ground-structure system
  - reinforcement of ground and soil structures, reinforcement of structural foundations

(further details: L-2-2)

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

37

## Improvement of properties of ground and soil structure

- Replacement
  - clean sand is replaced with silty sand or gravel
- Strengthen
  - use some kinds of chemical binder
  - deep mixing method (DMM)
- **Densification (*most common and economical*)**
  - sand compaction pile method (SCP)
  - dynamic consolidation method (DC)


2006/6/22

Mechanics of Geomaterials by J.  
Takemura

38

# Sand compaction method (SCP) and dynamic consolidation method (DC)

SCP サンド・コンパクション・パイル工法




DC 動圧密工法


2006/6/22

Mechanics of Geomaterials by J. Takemura

39



Ground improvement used  
in Port and Rokko islands




Note: Extent of zones treated by preloading may be inaccurate in size

2006/6/22

Mechanics of Geomaterials by J. Takemura

40

## Zone of liquefied area in Port Island at 1995 Hogueken-Nanbu Eq.




2006/6/22

Mechanics of Geomaterials by J.  
Takemura

41

## Increase in N-value due to treatment




by rod (vibro) compaction

2006/6/22

Mechanics of Geomaterials by J.  
Takemura

42

### Increase in N-value due to treatment




2006/6/22

Mechanics of Geomaterials by J. Takemura

43

### Comparison of ground subsidence in zones treated by different methods




2006/6/22

Mechanics of Geomaterials by J. Takemura


44



## Two types of ground improvement for the foundation of quay walls at Port Island phase II



## Displacements of quay wall founded on replaced sand and SCPs



2006/6/22

Mechanics of Geomaterials by J. Takemura

46

## Enhancement of drainage


- control of pore water pressure increase
  - gravel drain method
  - steel members with drainage function
- lowering ground water table
  - deep well method
  - drainage method

2006/6/22


Mechanics of Geomaterials by J. Takemura

47

### Enhancement of drainage (I) - vertical drains -



#### Generation of excess pore water pressure at P




2006/6/22

Mechanics of Geomaterials by J. Takemura

48

## Enhancement of drainage (I)

- Grand water table lowering method with deep wells -



2006/6/22

Mechanics of Geomaterials by J. Takemura

49

## Reinforcement of ground-structure system


- reinforcement of ground and soil structures
  - preventing shear deformation of soil
  - continuous wall method
  - sheet pile method
- reinforcement of structural foundations
  - increase the capacity of piles
  - reinforcement of spread footing
  - introduction of flexible joints

2006/6/22

Mechanics of Geomaterials by J. Takemura

50

## Reinforcement of ground with diaphragm walls



## Modification of seismic design considering liquefaction

EX)

- Quay wall design

(L-3-2)

- Bridge foundations (pile foundations)

(L-3-1)

**Key words: liquefaction, level 2 motion, lateral movement**

2006/6/22

Mechanics of Geomaterials by J. Takemura

52